LOWering

CAPEX by up to 75% material savings

with

Thermoformed Tube Settler Systems

for

Enhanced Sedimentation



Pavel Sorejs

Regional Sales Manger, Europe , Middle East, Africa Water & Waste Water

BRENTWOOD





Applications

Purpose and benefits

Thermoforming vs Extrusion

Thermoformed Tube Setters

Structural Testing

Thermoformed vs Extruded design

Case study

.. enhance settling via higher application overflow rates



BRENTWOOD & ARAMCO









Currently 8 manufacturing facilities worldwide





- 1. United States of America
- Argentina
- Australia
- Austria
- 5. Bahamas
- 6. Belgium
- 7. Brazil
- 8. Brunei
- 9. Canada (9 provinces)
- 10. Chile
- 11. China
- 12. Colombia
- 13. Czech Republic
- 14. Egypt
- 15. England
- 16. Finland Konaflex Oy, Vanta
- 17. France
- 18. Georgia
- 19. Germany
- 20. Greece
- 21. Guam
- 22. Hong Kong
- 23. RELAND
- 24. India. 25. Indonesia

26. Israel 27. Italy 28. Japan 29. Liechtenstein **30.** Lithuania 31. Luxembourg 32. Malaysia 33. Mexico 34. Mongolia 35. Morocco 36. Netherlands 37. New Zealand 38. Norway 39. Papua New Guinea **40.** Philippines 41. Poland 42. Portugal 43. Puerto Rico 44. Saudi Arabia

45. Scotland 46. Singapore 47. Slovakia 48. South Korea 49. Sri Lanka

50. St. Kitts, West Indies 1. Spain 52. Sweden 53. Switzerland 54. Taiwan 55. Thailand 56. Trinidad and Tobago 57. Turkey 58. United Arab Emirates 59. Wales 60. Venezuela 61. Virgin Islands

Tube Settler Applications

Potable water clarification Membrane pre-treatment **Desalinization pre-treatment Backwash reclamation Resin recovery** Wastewater secondary and tertiary clarification **Phosphorus removal** Acid mine drainage (AMD) ...enhance settling via higher application overflow rates



Tube Settler & "Lamellas"

Both increase the settling capacity of circular clarifiers and/or rectangular sedimentation basins by reducing the vertical distance a floc particle must settle before agglomerating to form larger particles.



Reduce the distance the particle has to drop to be removed from suspension

Distance <u>Without</u> Tube Settlers



Tube Settler Process Benefits Particle settling depth is less than conventional clarifiers/basins Expand the settling capacity of new or existing clarifiers/basins Higher flow rates

Less frequent filter backwash

Moderate turbidity spikes



Thermoforming vs Extrusion





Thermoformed

Extruded

Designed for Maximum Structural Integrity

Designed for Maximum Structural Integrity

- Precise Alignment
- Dedicated Glue Joints
- Edge Return
- Structural Ribs
- Wave Sheet

The Brentwood advantage: uniform load of 15-25 lbs/ft² & point load of 250 lbs on 1ft² (73-146 kgs/m² & point load of 113 kgs on .0929 m²)



Brentwood Structural Testing IFR-6024 – Three nested packs

Rich and and

Brentwood Structural Testing IFR-6024 – Initial Settings 2.95 #

2 35 #

Brentwood Structural Testing IFR-6024 – Uniform Load Added 1

₩₩ ₩₩ ₩₩ ₩₩ ₩₩

18

The second

Brentwood Structural Testing IFR-6024 – Point Load Start

9-

.10

111 - 11 - 1 -

0

apre

Brentwood Structural Testing IFR-6024 – Point Load Cont'd



Brentwood Tube Settler Structural Integrity Graph



1.1

TAXE &

1 23 23 34 36 38

Z.10#

100 colt and an

·682E1

ST. 10 44

1111

- and

95 #





3. Extruded profile designed in rectangular clarifiers



달

Brentwood Tube Settler Structural Integrity

IFR-6024 Tube Settler Module Average Deflection Nested with Accugrid Module Test



Brentwood Tube Settlers

Designed for Maximum Structural Integrity

- Precise Alignment
- Dedicated Glue Joints
- Edge Return
- Structural Ribs
- Wave Sheet

The Brentwood advantage: allows to meet a design load of 275 kg/0.1m2





Preciously designed engineered design allowing to apply a point load of **275 kg/0.1m2** over the unsupported mid span Standard Support system meets up to 20 cm discrepancies







PLAN VIEW: BRENTWOOD DESIGN NTS







3. Extruded profile designed in rectangular clarifiers



달





NSF Certification

All components for potable Brentwood Tube Settler Systems are available as NSF certified

Tested and Certified by NSF to ANSI/NSF Standard 61 "Drinking Water System Components"



Certified to ANSI/NSF 61



Key Take-aways

- No need for primary supports
- Engineering time and cost reduction
- 75% GRP, Super Duplex, SS supports material reduction
- 30% TCO savings,
- One of the strongest on the market designed around 275 kg/0.1m2

Thank you for your time!

Any questions?

